



VFIB00



User Manual

Caution: Fog machines may set off smoke alarms!

©2022 **ADJ Products, LLC** all rights reserved. Information, specifications, diagrams, images, and instructions herein are subject to change without notice. ADJ Products, LLC logo and identifying product names and numbers herein are trademarks of ADJ Products, LLC. Copyright protection claimed includes all forms and matters of copyrightable materials and information now allowed by statutory or judicial law or hereinafter granted. Product names used in this document may be trademarks or registered trademarks of their respective companies and are hereby acknowledged. All non-ADJ Products, LLC brands and product names are trademarks or registered trademarks of their respective companies.

ADJ Products, LLC and all affiliated companies hereby disclaim any and all liabilities for property, equipment, building, and electrical damages, injuries to any persons, and direct or indirect economic loss associated with the use or reliance of any information contained within this document, and/or as a result of the improper, unsafe, insufficient and negligent assembly, installation, rigging, and operation of this product.

Europe Energy Saving Notice

Energy Saving Matters (EuP 2009/125/EC)

Saving electric energy is a key to help protecting the environment. Please turn off all electrical products when they are not in use. To avoid power consumption in idle mode, disconnect all electrical equipment from power when not in use. Thank you!

INTRODUCTION

Introduction: Congratulations on your purchase of one of the most reliable fog machines on the market today! The VF1300 commercial fog machine has been designed to perform reliably for years when the guidelines in this booklet are followed. Please read and understand the instructions in this manual carefully and thoroughly before attempting to operate this unit. These instructions contain important information regarding safety during usage and maintenance.

Customer Support: ADJ Products, LLC provides a toll free customer support line, to provide set up help and to answer any questions that may arise during set up or initial operation. You may also visit us on the web at www.adj.com for any comments or suggestions. Service Hours are Monday through Friday 8:00 a.m. to 4:30 p.m. Pacific Standard Time.

Voice: (323) 582-2650
Fax: (323) 582-2941
E-mail: support@adj.com

To purchase parts online visit parts.adj.com.

Warning! To prevent or reduce the risk of electrical shock or fire, do not expose this unit to rain or moisture.

Caution! There are no user serviceable parts inside this unit. Do not attempt any repairs yourself, as doing so will void your manufacturer's warranty. In the unlikely event your unit may require service please contact ADJ Products, LLC.

SAFETY NOTICE! NEVER POINT OR AIM A FOG MACHINE TOWARDS PEOPLE OR THEIR CLOTHING. THIS UNIT EMITS HOT VAPOR AND SHOULD BE USED WITH THE SAME CARE THAT WOULD BE OBSERVED WHEN USING AN ELECTRIC KETTLE OR AN IRON.

Note: *Specifications and improvements in the design of this unit and this manual are subject to change without any prior written notice.*

PLEASE recycle the shipping carton when ever possible.

WARRANTY

MANUFACTURER'S LIMITED WARRANTY

- A. ADJ Products, LLC hereby warrants, to the original purchaser, ADJ Products, LLC products to be free of manufacturing defects in material and workmanship for a prescribed period from the date of purchase (see specific warranty period on reverse). This warranty shall be valid only if the product is purchased within the United States of America, including possessions and territories. It is the owner's responsibility to establish the date and place of purchase by acceptable evidence, at the time service is sought.
- B. For warranty service you must obtain a Return Authorization number (RA#) before sending back the product—please contact ADJ Products, LLC Service Department at 800-322-6337. Send the product only to the ADJ Products, LLC factory. All shipping charges must be pre-paid. If the requested repairs or service (including parts replacement) are within the terms of this warranty, ADJ Products, LLC will pay return shipping charges only to a designated point within the United States. If the entire instrument is sent, it must be shipped in its original package. No accessories should be shipped with the product. If any accessories are shipped with the product, ADJ Products, LLC shall have no liability whatsoever for loss of or damage to any such accessories, nor for the safe return thereof.
- C. This warranty is void if the serial number has been altered or removed; if the product is modified in any manner which ADJ Products, LLC concludes, after inspection, affects the reliability of the product; if the product has been repaired or serviced by anyone other than the ADJ Products, LLC factory unless prior written authorization was issued to purchaser by ADJ Products, LLC; if the product is damaged because not properly maintained as set forth in the instruction manual.
- D. This is not a service contract, and this warranty does not include maintenance, cleaning or periodic check up. During the period specified above, ADJ Products, LLC will replace defective parts at its expense with new or refurbished parts, and will absorb all expenses for warranty service and repair labor by reason of defects in material or workmanship. The sole responsibility of ADJ Products, LLC under this warranty shall be limited to the repair of the product, or replacement thereof, including parts, at the sole discretion of ADJ Products, LLC. All products covered by this warranty were manufactured after August 15, 2012, and bear identifying marks to that effect.
- E. ADJ Products, LLC reserves the right to make changes in design and/or improvements upon its products without any obligation to include these changes in any products theretofore manufactured.

No warranty, whether expressed or implied, is given or made with respect to any accessory supplied with products described above. Except to the extent prohibited by applicable law, all implied warranties made by ADJ Products, LLC in connection with this product, including warranties of merchantability or fitness, are limited in duration to the warranty period set forth above. And no warranties, whether expressed or implied, including warranties of merchantability or fitness, shall apply to this product after said period has expired. The consumer's and/or Dealer's sole remedy shall be such repair or replacement as is expressly provided above; and under no circumstances shall ADJ Products, LLC be liable for any loss or damage, direct or consequential, arising out of the use of, or inability to use, this product.

This warranty is the only written warranty applicable to ADJ Products, LLC Products and supersedes all prior warranties and written descriptions of warranty terms and conditions heretofore published.

MANUFACTURER'S LIMITED WARRANTY PERIODS:

- **Lighting Products = 1-year (365 days) Limited Warranty** (Such as: Special Effect Lighting, Intelligent Lighting, UV lighting, Strobes, Fog Machines, Bubble Machines, Mirror Balls, Par Cans, Trussing, Lighting Stands etc. excluding LED and lamps)
- **Laser Products = 90-Day Limited Warranty**
- **L.E.D. Products = 2-year (730 days) Limited Warranty** (excluding motors, PCB boards, and power supplies, which have a 1-year (365 day Limited Warranty) and batteries which have a 180 day limited warranty).

WARRANTY REGISTRATION

The VF1300 fog machine carries a one year (365 days) limited warranty. Please fill out the enclosed warranty card to validate your purchase. All returned service items, whether under warranty or not, must be freight pre-paid and accompanied by a return authorization (R.A.) number. The R.A. number must be clearly written on the outside of the return package. A brief description of the problem as well as the R.A. number must also be written down on a piece of paper and included in the shipping container. If the unit is under warranty, you must provide a copy of your proof of purchase invoice. You may obtain an R.A. number by contacting our customer support number.

SAFETY PRECAUTIONS

- In the event that the unit needs to be returned to ADJ Products, LLC for service, use only the original packaging and materials for shipping.
- To reduce the risk of electrical shock or fire, do not expose this unit to rain or moisture.
- Do not spill water or other liquids into or onto your device.
- Ensure that the fog fluid is contained inside the fluid reservoir only. Do not spill fog fluid into or onto other internal components of the device.
- Ensure that the power outlet used matches the device's required voltage.
- Do not remove the cover for any reason. There are no user serviceable parts inside this device!
- Disconnect the unit from main power when left unused for long periods of time.
- Never connect this device to a dimmer pack.
- Do not attempt to operate this unit if it has been damaged in any way.
- Never operate this unit with the cover removed.
- Do not attempt to operate this unit if the power cord has been frayed or broken.
- Do not attempt to remove or break off the ground prong from the electrical cord. This prong is used to reduce the risk of electrical shock and fire in the event of an internal short.
- Disconnect from main power before attempting to make any type of connection.
- Never block the ventilation holes, and always be sure to mount this unit in an area that will allow proper ventilation. Allow at least 6" (15cm) clearance between this device and a wall.
- This unit is intended for indoor use only, and use of this product outdoors voids all warranties.
- Follow proper storage guidelines when storing for extended periods. See the **Proper Storage and Maintenance** section of this manual for details.
- Always mount this unit in a safe and stable manner.
- Please route your power cord out of the path of foot traffic. Power cords should be routed so that they are not likely to be walked on or pinched by items placed upon or against them.
- The fixture should be serviced by qualified service personnel when:
 - A. The power-supply cord or the plug has been damaged.
 - B. Objects have fallen onto, or liquid has been spilled into, the unit.
 - C. The unit has been exposed to rain or water.
 - D. The unit does not appear to operate normally or exhibits a marked change in performance.

DESCRIPTION

This device features a revolutionary new heating element that has been specifically designed to prevent excessive particle build up that can cause premature fogger failure. This fog machine has a wide-angle spray nozzle and a long-life pump, both of which have been specially designed for high performance fogger output. Additionally, the fluid tank includes a fluid level sensor that automatically shuts down the device if low fluid level is detected, providing a safeguard against premature pump or device failure. A removable remote control device is also included.

SET UP

1. Open the shipping carton and carefully remove the unit. Be sure to remove all the packing material, paying particular attention to the area around the nozzle.
2. Set the machine on a flat dry surface. Remove the included bracket from the packaging and attach it to the sides of the fog machine using the supplied hardware. Please note that the bracket is easily detachable and is not required for table-top usage. However, when the device is installed in a suspended environment, use of the bracket is required.
3. Fill the fog fluid reservoir with ADJ brand fog juice only, then replace the cap.
4. Firmly plug the remote control unit into the remote control socket located on the back of the unit.
5. Plug the unit into a power supply that meets the voltage requirements. A red LED on the remote control will illuminate, indicating that the device is receiving power. The device will then begin warming up, which should take about seven minutes. When warmup is complete, the fluid reservoir will glow green, indicating that the unit is ready to emit fog.
6. Press the button on the remote to emit fog. Refer to the **Remote Operation** section of this manual for detailed information.

REMOTE OPERATION

Always be sure to maintain an adequate supply of ADJ® Brand Fog juice™ in the fluid reservoir. Running the fog machine dry will cause pump failure and/or clogging. This is the most common cause of failure in fog machines.

Remote Operation: Start by connecting the VF5PR remote to the fog machine. Once the machine is plugged in and powered on, it will begin warming up, which should take about seven (7) minutes. After the unit has warmed up, the fluid reservoir will glow green, indicating the unit is ready to emit fog. To emit fog, simply press and hold the button on the remote. The knob sets the amount of fog the machine will output.

If the fluid reservoir is glowing green and the unit does not emit fog after the button is pressed for 30 seconds, check that the fluid tank has a sufficient amount of fog fluid.

Caution: Disconnect from the power supply before removing or replacing the remote control unit.

Wireless Remote Control: The VF1300 can also be operated by wireless remote. Plug the receiver box into the wireless input. Select one of the four dip switches on the receiver, and flip it to the ON position, and locate the button on the remote with a number that matches the chosen dip switch. The device will now emit fog when this button is pressed.

For example: If dip switch #3 is flipped to the ON position, button 3 on the wireless remote will control fog output.

TIMER REMOTE

VFTR13 Timer Remote (Sold Separately): Start by connecting the remote to the fog machine. The remote's timer function allows fog to be emitted at designated intervals. The remote has three (3) L.E.D.s that indicate different functions.

- The YELLOW LED on the left indicates that the timer is active.
- The RED LED indicates that continuous fogging is active.
- The GREEN LED on the right is for manual fogging. Wait for the GREEN LED to light up, then press the button to commence manual fogging.

The remote also contains two rotary knobs.

- The Duration knob sets the timer duration (length of time for fog output).
- The Interval knob sets the fog output intervals (length of time between fog output bursts).

Caution: Disconnect the unit from power before removing or replacing the remote control unit.

FUSE REPLACEMENT

Disconnect the unit from its power source, then remove the power cord from the unit. Once the cord has been removed, locate the fuse holder inside the power socket. Insert a flat-head screw driver into the power socket and gently pry out the fuse holder. Remove the bad fuse and replace with a new one. Please note that the fuse holder also has a holder for a spare fuse.

PROPER STORAGE AND MAINTENANCE

Store your device only in a cool area, and cover the device to prevent dust buildup. When storing for long periods of time, it is highly advised to at least run the device every 3-4 months, as long periods of inactivity can severely shorten the operational life. Only run water based fog juice through your device. Never run plain water, vinegar, or any other liquid solution through your device, as running anything other than water based fog juice will cause severe damage.

TROUBLE SHOOTING

If you experience low fog output, pump noise, or no fog output at all, disconnect the device from power and discontinue use immediately. Do not continue to push the remote control's activation button, as this may damage the device. Check fluid level, the external fuse or breaker, and remote connection, and verify that the wall outlet is sending power. If none of these factors prove to be the cause of the problem, and the unit still fails to operate correctly, the unit may require service. Please contact customer support for further instructions. Please do not return the unit to your dealer without contacting customer support first.

SPECIFICATIONS

MODEL:	VF1300
Supply Voltage:	120V or 230V, 50/60 Hz (pre-set at factory, cannot be altered)
Heater:	1100W (US) 1300W (Europe)
Weight:	15 lbs. / 7 kgs.
Dimensions:	17.5" x 12.5" x 8" 445mm x 315mm x 200mm
Fuse:	15A (120V) / 8A (230V)
Warm Up Time:	7 minutes
Tank Capacity:	2.3 Liters
Fluid Consumption:	60 mL per minute
Output:	12,000 cubic feet per minute
Fluid Type:	Water-based ADJ fog juice
Duty Cycle:	Not to exceed 6 hours powered on

ADJ Products, LLC
6122 S. Eastern Ave. Los Angeles, CA 90040 USA
Tel: 323-582-2650 / Fax: 323-725-6100
Web: www.adj.com / E-mail: info@adj.com

Follow Us On:



facebook.com/americanadj
twitter.com/americanadj
youtube.com/adjlighting

A.D.J. Supply Europe B.V.
Junostraat 2
6468 EW Kerkrade
Netherlands
service@adjgroup.eu / www.adj.eu
Tel: +31 45 546 85 00 / Fax: +31 45 546 85 99

